

ZAKŁAD CERTYFIKACJI**CERTIFICATE No. 14/21/Z
of Conformity to European Directive**

Certification program acronym – PDCWPA

Name and address
of the certificate owner: HEAT DECOR Spółka z ograniczoną odpowiedzialnością
ul. Gromadzka 54, 30-719 KrakówName and address
of the manufacturer: HEAT DECOR Spółka z ograniczoną odpowiedzialnością
ul. Gromadzka 54, 30-719 Kraków

Place of production: Korea

Product: Heating foil HEAT DECOR intended for rooms heating
230V, 50Hz, kl. II, IPX7 according to enclosure**The product meet requirements of the Low Voltage Directive
2014/35/UE**


Assessment of conformity was conducted on the basis of:

- Testing in scope of the harmonized standards:
PN-EN 60335-1:2012+A11:2014 (IDTEN 60335-1:2012/A11:2014),
PN-EN 60335-2-96:2005+A2:2009 (IDT EN 60335-2-96:2002/A2:2009) according to the Testing Reports No B/2021/56 of 03.03.2021 conducted by the Accredited Laboratory.
- Results of the inspection of organizational technical conditions conducted by accredited authorized and notified body for certification - according to the Report No 113/2019 of 11.10.2019.


The right to use the certificate includes the period from 10.03.2021 to 09.03.2026

and refers exclusively to products with identical properties (parameters) to the tested model and which meet requirements mentioned above.

DYREKTOR DS. CERTYFIKACJI


dr inż. Tomasz Włodek

PREZES ZARZĄDU


mgr inż. Edward Makiela

Katowice, 10.03.2021

**Enclosure
to the Certificate No. 14/21/Z
of 10.03.2021**

Heating foil models of HD-G series:

HD310G - width 1000 mm, thickness 0,338 mm

HD308G - width 800 mm, thickness 0,338mm

HD305G - width 500 mm, thickness 0,338 mm

HD303G - width 300 mm, thickness 0,338 mm

HD3025G - width 250 mm, thickness 0,338 mm

Heating foil power per running meter				
HD310G	HD308G	HD305G	HD303G	HD3025G
100 W/m	100 W/m	100 W/m	100 W/m	100 W/m
87,5 W/m	87,5 W/m	87,5 W/m	87,5 W/m	87,5 W/m
75 W/m	75 W/m	75 W/m	75 W/m	75 W/m
62,5 W/m	62,5 W/m	62,5 W/m	62,5 W/m	62,5 W/m
55 W/m	55 W/m	55 W/m	55 W/m	55 W/m
50 W/m	50 W/m	50 W/m	50 W/m	50 W/m
47,5 W/m	47,5 W/m	47,5 W/m	47,5 W/m	47,5 W/m
45 W/m	45 W/m	45 W/m	45 W/m	45 W/m
42,5 W/m	42,5 W/m	42,5 W/m	42,5 W/m	42,5 W/m
40 W/m	40 W/m	40 W/m	40 W/m	40 W/m
37,5 W/m	37,5 W/m	37,5 W/m	37,5 W/m	37,5 W/m
35 W/m	35 W/m	35 W/m	35 W/m	35 W/m
32,5 W/m	32,5 W/m	32,5 W/m	32,5 W/m	32,5 W/m
30 W/m	30 W/m	30 W/m	30 W/m	30 W/m
27,5 W/m	27,5 W/m	27,5 W/m	27,5 W/m	27,5 W/m
25 W/m	25 W/m	25 W/m	25 W/m	25 W/m
22,5 W/m	22,5 W/m	22,5 W/m	22,5 W/m	22,5 W/m
20 W/m	20 W/m	20 W/m	20 W/m	20 W/m
17,5 W/m	17,5 W/m	17,5 W/m	17,5 W/m	17,5 W/m
15 W/m	15 W/m	15 W/m	15 W/m	15 W/m
12,5 W/m	12,5 W/m	12,5 W/m	12,5 W/m	12,5 W/m
10 W/m	10 W/m	10 W/m	10 W/m	10 W/m
7,5 W/m	7,5 W/m	7,5 W/m	7,5 W/m	7,5 W/m

Heating foil models of HD-EPL series:

HD-EPL100 - width 1000 mm, thickness 0,450 mm

HD-EPL80 - width 800 mm, thickness 0,450 mm

HD-EPL50 - width 500 mm, thickness 0,450 mm

HD-EPL30 - width 300 mm, thickness 0,450 mm

HD-EPL25 - width 250 mm, thickness 0,450 mm

Heating foil power per running meter				
HD-EPL100	HD-EPL80	HD-EPL50	HD-EPL30	HD-EPL25
400 W/m	320 W/m	200 W/m	280 W/m	100 W/m
350 W/m	280 W/m	175 W/m	245 W/m	87,5 W/m
300 W/m	240 W/m	150 W/m	210 W/m	75 W/m
250 W/m	200 W/m	125 W/m	175 W/m	62,5 W/m
220 W/m	176 W/m	110 W/m	154 W/m	55 W/m
200 W/m	160 W/m	100 W/m	140 W/m	50 W/m
190 W/m	152 W/m	95 W/m	133 W/m	47,5 W/m
180 W/m	144 W/m	90 W/m	126 W/m	45 W/m
170 W/m	136 W/m	85 W/m	119 W/m	42,5 W/m
160 W/m	128 W/m	80 W/m	112 W/m	40 W/m
150 W/m	120 W/m	75 W/m	105 W/m	37,5 W/m
140 W/m	112 W/m	70 W/m	98 W/m	35 W/m
130 W/m	104 W/m	65 W/m	91 W/m	32,5 W/m
120 W/m	96 W/m	60 W/m	84 W/m	30 W/m
110 W/m	88 W/m	55 W/m	77 W/m	27,5 W/m
100 W/m	80 W/m	50 W/m	70 W/m	25 W/m
90 W/m	72 W/m	45 W/m	63 W/m	22,5 W/m
80 W/m	64 W/m	40 W/m	56 W/m	20 W/m
70 W/m	56 W/m	35 W/m	49 W/m	17,5 W/m
60 W/m	48 W/m	30 W/m	42 W/m	15 W/m
50 W/m	40 W/m	25 W/m	35 W/m	12,5 W/m
40 W/m	32 W/m	20 W/m	28 W/m	10 W/m
30 W/m	24 W/m	15 W/m	21 W/m	7,5 W/m

Heating foil models of HD-PRO series:

HD-PRO100 - width 1000 mm, thickness 0,500 mm

HD-PRO80 - width 800 mm, thickness 0,500 mm

HD-PRO50 - width 500 mm, thickness 0,500 mm

HD-PRO30 - width 300 mm, thickness 0,500 mm

HD-PRO25 - width 250 mm, thickness 0,500 mm

Heating foil power per running meter				
HD-PRO100	HD-PRO80	HD-PRO50	HD-PRO30	HD-PRO25
320 W/m	320 W/m	200 W/m	280 W/m	100 W/m
280 W/m	280 W/m	175 W/m	245 W/m	87,5 W/m
240 W/m	240 W/m	150 W/m	210 W/m	75 W/m
200 W/m	200 W/m	125 W/m	175 W/m	62,5 W/m
176 W/m	176 W/m	110 W/m	154 W/m	55 W/m
160 W/m	160 W/m	100 W/m	140 W/m	50 W/m
152 W/m	152 W/m	95 W/m	133 W/m	47,5 W/m
144 W/m	144 W/m	90 W/m	126 W/m	45 W/m
136 W/m	136 W/m	85 W/m	119 W/m	42,5 W/m
128 W/m	128 W/m	80 W/m	112 W/m	40 W/m
120 W/m	120 W/m	75 W/m	105 W/m	37,5 W/m
112 W/m	112 W/m	70 W/m	98 W/m	35 W/m
104 W/m	104 W/m	65 W/m	91 W/m	32,5 W/m
96 W/m	96 W/m	60 W/m	84 W/m	30 W/m
88 W/m	88 W/m	55 W/m	77 W/m	27,5 W/m
80 W/m	80 W/m	50 W/m	70 W/m	25 W/m
72 W/m	72 W/m	45 W/m	63 W/m	22,5 W/m
64 W/m	64 W/m	40 W/m	56 W/m	20 W/m
56 W/m	56 W/m	35 W/m	49 W/m	17,5 W/m
48 W/m	48 W/m	30 W/m	42 W/m	15 W/m
40 W/m	40 W/m	25 W/m	35 W/m	12,5 W/m
32 W/m	32 W/m	20 W/m	28 W/m	10 W/m
24 W/m	24 W/m	15 W/m	21 W/m	7,5 W/m

DYREKTOR DS. CERTYFIKACJI


dr inż. Tomasz Włodek



PREZES ZARZĄDU


mgr inż. Edward Makiela